

SERIES DIESEL STATIONARY

MODEL	DISPLACEMENTS		FAD		MAX	MOTOR	PHASE	RECEIVER	DIMENSIONS			KG
	CFM	LTS	CFM	LTS	PSI - BAR				LITRES	L	W	
AS20D-Y	20.0	566	13.4	379	150 - 10.0	4.7 -----	N/A	110	1320	430	991	95
AS20D-Y/ES	20.0	566	13.4	379	150 - 10.0	4.7 -----	N/A	110	1320	430	991	95
AS30D-Y/ES	30.0	850	22.5	637	150 - 10.0	10.0 -----	N/A	110	1320	480	1170	111

SPECIFICATIONS ARE SUBJECT TO ALTERATION WITHOUT PRIOR NOTICE

Features

INDUSTRIAL DUTY RATED - BRITISH AIR RECEIVERS - HIGH EFFICIENCY AIR PUMPS - LOW VIBRATION LEVELS
DEEP FINNED CAST IRON CYLINDER - RECOIL/ELECTRIC START - EASY INSTALLATION - SPARES & SERVICE NATIONWIDE
BALANCED FLYWHEEL/MULTIBLADE FAN FOR EFFICIENT COOLING - MINIMUM MAINTENANCE COSTS - EXPORTS WORLDWIDE