

### SERIES PETROL - STATIONARY

MODEL	DISPLACEMENTS		FAD		MAX	MOTOR	PHASE	RECEIVER	DIMENSIONS			KG
	CFM	LTS	CFM	LTS	PRESSURE				LITRES	L	W	
AS12P	12.0	340	8.4	238	150	4.0-----	N/A	110	1320	430	850	81
AS20P	20.0	566	13.4	379	150	5.5-----	N/A	110	1320	430	910	84
AS25P	25.0	708	18.0	510	150	8.0-----	N/A	110	1320	460	960	111
AS30P	30.0	850	22.5	637	150	11.0-----	N/A	110	1320	480	1120	128
AS25P-ES	25.0	708	18.0	510	150	8.0-----	N/A	110	1320	460	960	111
AS30P-ES	30.0	850	22.5	637	150	11.0-----	N/A	110	1320	480	1120	128
AS40P-ES	38.0	1076	28.5	8.7	150	13.0-----	N/A	110	1320	480	1120	128

**SPECIFICATIONS ARE SUBJECT TO ALTERATION WITHOUT PRIOR NOTICE**

**Features**

**INDUSTRIAL RATED - BRITISH AIR RECEIVERS - HIGH EFFICIENCY AIR PUMPS - LOW VIBRATION LEVELS**  
**CONFORMS TO EU NOISE REGULATIONS - GENIE UNLOADER CONTROL - SPARES & SERVICE NATIONWIDE**  
**TOTALLY ENCLOSED BELT GUARD FOR UTMOST SAFETY - EXPORTS WORLDWIDE (A24 - A30 SERIES THERMAL PROTECTION TO ALL MOTORS)**