

**SERIES WORKSHOP / COMMERCIAL**

MODEL	DISPLACEMENTS		FAD		MAX	MOTOR	PHASE	RECEIVER	DIMENSIONS			KG
	CFM	LTS	CFM	LTS	PSI - BAR	HP - KW		LITRES	L	W	H	
A6/50	6.0	170	3.6	102	125 - 8.5	1.5 - 1.1	1	50	1085	340	720	49
A10/50-1	9.0	255	5.4	153	150 -10.0	2.0 - 1.5	1	50	1085	340	720	55
A10/110-1	9.0	255	5.4	153	150 -10.0	2.0 - 1.5	1	110	1320	370	770	75
A15/110-1	15.0	425	10.3	292	150 -10.0	3.0 - 2.2	1	110	1320	370	775	84
A15/160-1	15.0	425	10.3	292	150 -10.0	3.0 - 2.2	1	160	1580	380	880	94
A18/160-1	16.0	453	12.0	339	150 -10.0	3.0 - 2.2	1	160	1580	390	890	97
A18/210-1	16.0	453	12.0	339	150 -10.0	3.0 - 2.2	1	210	1640	460	930	125
A20/210-1	20.0	566	13.4	372	150 -10.0	4.0 - 3.0	1	210	1640	460	930	131
A6/50-3	6.0	170	3.6	102	125 - 8.5	1.5 - 1.1	3	50	1085	340	720	49
A10/50-3	9.0	255	5.4	153	150 -10.0	2.0 - 1.5	3	50	1085	340	720	55
A10/110-3	9.0	255	5.4	153	150 -10.0	2.0 - 1.5	3	110	1320	370	770	75
A15/110-3	15.0	425	10.3	292	150 -10.0	3.0 - 2.2	3	110	1320	370	775	84
A15/160-3	15.0	425	10.3	292	150 -10.0	3.0 - 2.2	3	160	1580	380	880	94
A18/160-3	16.0	453	12.0	339	150 -10.0	3.0 - 2.2	3	160	1580	390	890	97
A18/210-3	16.0	453	12.0	339	150 -10.0	3.0 - 2.2	3	210	1640	460	930	125
A23/210-3	22.0	623	15.4	436	150 -10.0	5.5 - 4.0	3	210	1640	460	1000	155
A25/210-3	25.0	708	18.0	510	150 -10.0	5.5 - 4.0	3	210	1640	460	1000	163
A26/210-3	26.0	736	20.0	566	150 - 10.0	5.5 - 4.0	3	210	1640	460	1150	174
A30/250-3	30.0	850	22.5	637	150 -10.0	7.5 - 4.0	3	250	1650	490	1200	213
A50/250-3	42.0	1189	31.5	892	150 -10.0	10.0 - 7.5	3	250	1650	490	1290	256
A70/350-2	60.0	1699	45.0	1274	150 -10.0	15.0 - 11.0	3	350	1930	600	1270	354
A100/350-3	80.0	2265	60.0	1699	150 -10.0	20.0 - 15.0	3	350	1930	600	1340	412

***SPECIFICATIONS ARE SUBJECT TO ALTERATION WITHOUT PRIOR NOTICE***

**Features**

**INDUSTRIAL DUTY RATED - BRITISH AIR RECEIVERS - HIGH EFFICIENCY AIR PUMPS - LOW VIBRATION LEVELS**  
**AUTO STOP/START - MOTORS HEAVY DUTY IP55 - SPARES & SERVICE NATIONWIDE**  
**DEEP FINNED CAST IRON CYLINDER - EXPORTS WORLDWIDE**