

BREATHING AIR SYSTEM

AL / ALSD

[Return
to
Index](#)



Standard equipment

Compressed air purification for breathing air complying to AS 2299, ANSI Z86 and EN 12021.

Complete purification system consisting of ZANDER-Microfilter, XP series prefilter ordered separately

Data is based on the following conditions :

Pressure rating 7 bar e Max 10 bar e Min 4 bar g

Inlet Temperature 20°C

Ambient Temperature 25°C

Normal Dewpoint -50°C

Type	Capacity CFM(inlet)	No of Masks *	Cartridge	Max pressure	Base unit Price (€)	Prod. group	Optional pre filter ** Adder	Pre filter Price (€) Adder	Prod. group
AL1	8	1	2/6CD	10	1,027	05ZH29	G2XP	120.51	05ZH29
AL2	16	2	2/12CD	10	1,189	05ZH29	G2XP	120.51	05ZH29
AL3	22	3	2/18CD	10	1,366	05ZH29	G2XP	120.51	05ZH29
AL4	31	4	2/24CD	10	3,205	05ZH29	G3XP	145.23	05ZH29
AL5	39	5	2/30CD	10	3,404	05ZH29	G5XP	167.89	05ZH29
AL6	47	6	2/36CD	10	3,569	05ZH29	G7XP	203.94	05ZH29
ALSD30	24	3	HSW2	10	3,205	05ZH29	G2XP	120.51	05ZH29
ALSD60	44	5	2/36CR	10	4,623	05ZH29	G7XP	203.94	05ZH29
ALSD85	61	8	2/50CR	10	5,240	05ZH29	G7XP	203.94	05ZH29
ALSD125	92	12	4/36CR	10	7,088	05ZH29	G9XP	307.97	05ZH29
ALSD170	122	15	4/50CR	10	7,644	05ZH29	G9XP	307.97	05ZH29
ALSD250	183	25	6/50CR	10	9,861	05ZH29	G11XP	360.5	05ZH29